




















World-wide competence











Your dealer:

Heisplan

Vestre Bingsa Industrivei 7 6019 Ålesund Tlf: 95 17 17 00

Web: www.heisplan.no
Email: post@heisplan.no



GEDA-Dechentreiter GmbH & Co. KG

Mertinger Straße 60 D-86663 Asbach-Bäumenheim Phone +49 (0) 906 9809-0 Fax +49 (0) 906 9809-50 info@geda.de www.geda.de Heisplan **ROPE HOISTS** Mini 60 S Maxi 120 S

Maxi 150 S

Ideal for scaffolders, decorators and facade fabricators!

The quick and safe hoist for transporting material on a scaffold.




The handy helper for scaffolding

GEDA scaffold hoists offer great advantages primarily thanks to quick assembly and rapid conversion. The handy rope drum drive is easily secured at the bottom of the scaffold while the lightweight swivel arm is attached at the top of the scaffold at the desired height. The maximum working height is 40 m, reaching up to 76 m when the winch is set higher.





Lifting speed



51/81 m 0,25/0,75 kW/ 230 V/50 Hz 23/69 m/min.

GEDA Maxi 120 S


Load capacity 120 kg Lifting height 40/76 m 51/81 m Rope length **Electrical** 0,45/1,35 kW/ 230 V/50 Hz power supply 20/60 m/min. Lifting speed

GEDA Maxi 150 S

Load capacity 150 kg Lifting height 40/76 m 51/81 m Rope length **Electrical** 0,45/1,35 kW/ 230 V/50 Hz power supply 15/45 m/min. Lifting speed













Safety

- 1) Easy placement of the rope on the swivel arm without having to dismantle the rollers
- 2 The motor stops when the rope slackens; the rope remains tight on the drum
- 3 An integrated limit switch turns it off on reaching the swivel arm, when overloaded or caught on the scaffold

Numerous load carrying devices ...

... make it easy to transport scaffold components/parts, as well as decorator supplies and insulating materials.